

PRODUCT DATA SHEET

PRIMERS



SELLACRYL 5x1

HIGH-SOLIDS, HIGH CONCENTRATION ECOLOGIC ACRYLIC PRIMER

DESCRIPTION

SELLACRYL 5X1 is an ecologic, LEED certified, concentrated, specially formulated styrene - acrylic primer that prepares most exterior surfaces for finish coats. It provides maximum breathability, adhesion, mildew resistance and holdout to prolong the life of the finish. It increases surface spread rate for any coating applied on top of it. Easily applicable, with great adherence, non-flammable, non-toxic, anti-fungi. It possesses very high adherence, hardness, and protection to a great variety of surfaces. It is 1-2 dichlorobenzene, Alkyl phenol, formaldehyde, lead, mercury, chromium, antimonium, triphenyl tin and tributyl tin free.

APPLICATION / RECOMMENDED USES

Liquid primer for any concrete, masonry block, brick, stucco, plywood, etc. surface. It prepares the surface for any latex coating, texture coating and roof coating. When diluting mix perfectly to obtain a homogeneous mixture.

AVAILABLE PRESENTATIONS

1 liter
1 gallon
5 gallons
200 liters.

SURFACE SPREAD AREA

-FOR LATEX PAINTS: 31 – 42 sq. meters per liter, diluted with 5 parts of water for every 1 part of primer.
-FOR LATEX TEXTURIZED COATING: 20 - 24 sq. meters per liter, diluted with 3 parts of water for every 1 part of primer.
-FOR ACRYLIC ROOF COATING: 13 – 16 sq. meters per liter, diluted with 2 parts of water for every 1 part of primer.

APPLICATION

Clean the surface perfectly leaving it grease and dust free. If needed, the surface must be sanded and / or brushed before primer to ensure a clean and proper surface. Use a coat of **SELLACRYL 5X1**.

RECOMMENDATIONS

-Do not mix with any other products.
-Do not leave any container without its lid or in the sun.
-Wash your brushes and tools with water.

STORAGE

It can be stored in a dry, dark, and fresh place for up to one year as long as it is perfectly sealed in its original container. Do not store **SELLACRYL 5X1** if it has already been diluted.

WARRANTY

PINTEX warrants the quality of its products according to its specifications. **SELLACRYL 5X1** has warranty as long as it is used following every recommendation made by **PINTEX**. Recommendations, yields, and suggestions enlisted above do not represent a warranty.

TECHNICAL DATA

VOC (NOM-123-SEMARNAT-1998)	Less than 50 g/L
BROOKFIELD VISCOSITY (ASTM D 2196)	27,000 - 35,000
DENSITY (ASTM D 1475)	1.02 - 1.06 g/mL
SOLIDS BY WEIGHT (ASTM D 1644)	34 - 36
SOLIDS BY VOLUME	35 %
PH (ASTM E 70)	8 - 9.5

Data referred to in this Sheet is based solely on our experience. **PINTEX** is not responsible for any flaws or damages caused by existing conditions, whether on the surface or on the building itself. We recommend making tests before applying the products on any particular application. The warrantee is limited only to the exchange of the material to fix any flaw, not including labor or any other additional costs. The information contained herein may be changed without any prior notice.

Elaboration: 23 May 2003
Check day: 24 October 2022

PINTURAS Y TEXTURIZADOS, S.A. DE C.V.

Av. Vía Dr. Gustavo Baz Prada No. Ext. 3826 Col. San Nicolás
Tlalnepantla de Baz, Edo. de México C.P. 54030

Tel: 55-5565-3534
Del interior: 800-836-9734

info@pintex.com.mx

www.pintex.com.mx