

# SANDLASTIC

## COLORED PEBBLE TEXTURE COATING

### DESCRIPTION

**SANDLASTIC** is colored pebble textured coating made with elastomeric acrylic resins, quartz and marble sands, inorganic pigments and various chemical additives. It is manufactured with integrated color and ready to use, you can obtain smooth textures.

### USAGE

As a decorative and protective coating, for both, interior and exterior surfaces. It can be applied on all kind of substrates, such as gypsum, gypsum board, concrete, wood, masonry, etc.

### ADVANTAGES

- U.V. stable.
- Very hard, seamless film, high resistance.
- Weather resistant.
- Easy and fast to install.
- 100 % washable.
- Non toxic.

### PACKAGE

28 Kgs. Pails.

### TEXTURES

You can obtain either smooth or rough textures depending on installation procedures.

### COVERAGE

From 11 to 16 M2 per pail.

### DRYING TIME

Set: 4 hours.  
 Hard: 24 hours.  
 Cured: 20 days.  
 Time may vary depending on weather conditions.

### COLORS

880 colors to choose from.

### PREPARATION

**SANDLASTIC** is ready to use, just mix it perfectly, do not add any other material.

### APPLICATION

The Surface to be covered must be completely smooth.

Clean the Surface to remove grease or dust.

First apply a coat of **SELLACRYL 5X1** mixed with **VINILPYT** acrylic Paint in the same color as the **SANDLASTIC** to seal the surface.

Roughly apply an even coat of **SANDLASTIC** to a thickness slightly thicker than the largest aggregate size. Then pull across the rough application coat using a horizontal trowel motion and develop a uniform thickness no greater than the largest aggregate of the material. Apply the **SANDLASTIC** using the desired tool, trowel, brush or hopper gun.

### RECOMENDATIONS

- Do not apply on surfaces with temperatures below 7°C or higher than 40°C.
- Apply on full walls.
- Do not mix with any other materials.
- Do not leave within reach of children.
- Wash tools with clean water.

### STORAGE

**SANDLASTIC** must be stored at a minimum of 40 °F (4 °C) and a maximum of 100 (38 °C) in tightly sealed containers protected from weather and out of direct sunlight.

### WARRANTY

**PINTEX** guaranties the constant quality of all its products, according to their manufacturing and technical specifications.

**SANDLASTIC** is guaranteed for a 5 year period against color fading or peeling, always under normal conditions.

PHYSICAL PROPERTIES	SPECIFICATION
VOC'S	Less than 35 g/l.
VISCOSITY	40,000 - 50,000 cps
DENSITY	1.90 - 2.05
% SOLIDS	77 - 81 %
PH	8.0-9.5

Data referred to in this Sheet is based solely on our experience. **PINTEX** is not responsible for any flaws or damages caused by existing conditions, whether on the surface or on the building itself. We recommend making tests before applying the products on any particular application. The warrantee is limited only to the exchange of the material to fix any flaw, not including labor or any other additional costs. The information contained herein may be changed without any prior notice.

**Elaboration:** 18 July 2006  
**Check day:** 25 March 2024