

PRODUCT DATA SHEET

LATEX PAINTS



DURACOLOR 10 YEARS FLAT STYRENE - ACRYLIC LATEX TOP COAT

DESCRIPTION

DURACOLOR 10 YEARS is a styrene-acrylic latex paint offering flat top coat superior weather resistant finish, and years of lasting protection. It levels beautifully to a smooth lustrous sheen with maximum breathability, color retention. It possesses very high adherence, hardness, and protection to a great variety of surfaces. Non-toxic, non-flammable, anti-fungi product.

USES

As a final protective and decorative coating on walls and ceilings of concrete, acrylic textured finishes, stucco, brick, gypsum board, etc.

AVAILABLE PRESENTATIONS

1 liter
1 gallon
5 gallons
200 liters.

SURFACE SPREAD RATE

3.7 to 5.7 sq. meters per liter applying two coats. This yield may vary depending on surface conditions.

COLORS

There are 880 different colors to choose from. It can also be matched to any desires color using our highly technologic color-matching system.

DILUTION

It can be diluted up to 15% with clean water. Make sure to mix perfectly.

PREPARATION

DURACOLOR 10 YEARS comes ready to use, just needs to mix it thoroughly.

APPLICATION

-Clean the surfaces from dust and grease. Apply a coat of **SELLACRYL 5X1** acrylic primer at least 4 hours prior to application.
-Apply **DURACOLOR 10 YEARS** in an even continuous coat using typical painting tools. If necessary apply a second coat after the first one dries.
-Small amounts of clear water may be used to thin **DURACOLOR 10 YEARS** to adjust workability.

RECOMMENDATIONS

Do not mix with any other products. Do not leave any container without its lid or in the sun.
Wash your brushes and tools with water.

STORAGE

It can be stored in a dry, dark, and fresh place for up to one year as long as it is perfectly sealed in its original container. Do not store **DURACOLOR 10 YEARS** if it has already been diluted.

WARRANTY

PINTEX warrants the quality of its products according to its specifications. **DURACOLOR 10 YEARS** has a 10 year warranty as long as it is used following every recommendation made by **PINTEX**. Recommendations, yields, and suggestions enlisted above do not represent a warranty.

TECHNICAL DATA

VOC (g/L) NOM-123-SEMARNAT-1998	Less than 50
AROMATIC VOLATILE COMPOUND CONTENT	NOT PRESENT
BROOKFIELD VISCOSITY (CPS) ASTM- D 2196	7,000 – 8,000
DENSITY (G/ML) ASTM - D 1475	1.36 - 1.38
% SOLIDS BY WEIGHT ASTM - D 1644	49 - 51
SOLIDS BY VOLUME	30 - 31
PH ASTM - E 70	8 – 9.5
DRYING TIME TO (MIN) TOUCH ASTM D 1640	60
FINENESS, HEGMAN ASTM - D1210	5 H
% ADHERENCE (ASTM D 3359)	Higher than 75
% HIDING POWER ASTM-D2805-96	94
FLEXIBILITY ASTM-D522-93	It doesn't present cracking neither detachment
WASHING CYCLES NMX-C-423-ONNCC-2003	5,000 Cycles without wear
SALINE CHAMBER (ASTM B 117)	Does Not Present Wear In 150 Hours
ACCELERATED INTEMPERISM QUV	Does Not Present Wear In 200 Hours

Data referred to in this Sheet is based solely on our experience. **PINTEX** is not responsible for any flaws or damages caused by existing conditions, whether on the surface or on the building itself. We recommend making tests before applying the products on any particular application. The warrantee is limited only to the exchange of the material to fix any flaw, not including labor or any other additional costs. The information contained herein may be changed without any prior notice.

Elaboration: 23 May 2003
Check day: 21 August 2026

PINTURAS Y TEXTURIZADOS, S.A. DE C.V.



Av. Vía Dr. Gustavo Baz Prada No. Ext. 3826 Col. San Nicolás
Tlalnepantla de Baz, Edo. de México C.P. 54030



Tel: 55-5565-3534
Del interior: 800-836-9734



info@pintex.com.mx

www.pintex.com.mx